## Contributed by Leo J. McDonough USNS LCPL Roy M. Wheat (T-AK 3016) Vessel Particulars

Call Sign: NROY UIC: N23068 JNAP: BRITTLE USCG Official Number: 1073560 MSC Designator: T-AK 3016 IMO #: 8523137 Builder: Chernomorski Shipyard, Ukraine Hull 234 - Year 1987 Conversion: Bender SY, Mobile, AL. Hull 6875 - Year 2001 Type: RO/RO, Container Carrier Class: ABS ABS ID#: 36138RC

LOA:	864'	263.34 M
Length BP:	787' 04"	240.00 M
Breadth Molded:	98' 05"	30.00 M
Max Depth:	68' 10 <sup>3</sup> /4"	21.00 M
Max Draft:	34' 11"	11.285 M
Air Draft:	167'- Draft	50.9M - Draft

Tonnage:	Gross: 44,301	Net: 15,804		
Suez Tonnage:	Gross: 46,173	Net: 39,566		
Panama Canal:		Net: 36,570		
Lightship:	25,894	.55 MT		
Deadweight @ M	lax Draft: 30,366	Long Tons	2.00	
Displacement:	50,277	Long Tons		
Design Speed:	22.0 K	ts (MSC Charter S	peed 17.0 Kts)	
Engine HP (Twin	engine): TOTAL HP	is 38,400 Ahead	10,000 Astern	17.45
Screws: Twin Re	versible Screws (inbo	ard turning ahead)	,	
Single Rudder An	nidships			
Bow Thruster: 12	34 HP Kawasaki	Stern Thrust	er: 872 HP KaMeWa	
Anchor: 12 shots	Port & Stbd Anch	nors are 23,100 lb (	(10.5 mt) Stockless Bow	ver

## **Cargo Information**

Container Capacity: 969 TEU (261 are special purpose) Number of hatches: 6 Number of Holds: 12 Total Deck Area: 220,067 Sq. Total Cargo Deck Area: 193,207 Sq. Environmentally Controlled Cargo Area: 150,249 Sq.' RORO Deck Area: 114,924 Sq.' Max load distribution: 660 lb./sq.' except 330 lb./sq.' on top deck hatch covers Crane Capacity: AFT- 72 LT at 130' outreach. <u>Max</u> 113 LT at 95' outreach. FWD- 26 LT at 130' outreach <u>Max</u> 42 LT at 65' outreach Ramp Capacity: 160,000lbs (80 tons) Ramp Foot Pressure: < 500 lb./sq.' Load Factor for Sea State 3: 1.05